

# Magazine cum Bareboard Loader (2 in 1)

**First of its kind !**



Patent Pending

**Automatic feed from stack-up bare boards or semi-finished PCBAs from magazine. Maximum space utilization. Pre-setting up and loading minimises production downtime. Especially useful for running double sided PCBAs.**

Machine Specifications	
Model:	MBL2008
Machine External Dim. (mm)	Lg 1300 x W1450 x Ht 1250 (Msize) excluding light tower ht.
PCB max size (mm)	Lg. 330xW250 (Msize)
Magazine Capacity	Standard 2 Top-Bottom 2
Bare PCB stack up ht.	max. 220mm
Change over mode	by selector switch.
Magazine Change Over Time	approx: 35 secs
PCB Feed Pitch	Via selector switch in steps of 10, 20, 30, 40. 50mm
PCB Transfer Height	910+/-30mm
Cycle time	less than 10 secs.
Controls	PLC
Buzzer	M/c error mode , emergency switch and No incoming magazine buffer.
Light Tower	3 colour light tower with fault detections
Interfacing	SNEMA
Machine colour (Standard)	Powder coated rough surface finish light grey code 9174
Power (Kva)	220Vac/1 phase or 110V/1 phse. (500KVA)
Air Pressure:	Min. 4 bars
Options:	Other size available on request.
	When ordering please specify flow direction and rail fix position.