

V-Groove Depaneliser

**Separate boards without stress on components.
No more damaged components**



Front support panel with adjustable height to cater for PCBA with top and bottom components.

Separates PCBA Stress Free without damaging to SMT Components. Easy to use, fast , quiet and efficient !
Suitable for PCBA with continuous V-Groove cuts or with breaks in between. Flat belt conveyor transfer separated boards or breakaway webs out of the cutting area.
Safe with cutter protection.

Specifications Model: M-520	
Dimensions/Weight	Lg. 950 x W600 x Ht 465 mm Weight:90kgs.
Depanelise Stroke Lg.	Adjustable via touch screen from max.500mm to min. 10mm
Max/Min PCB Thickness	Max. 2.5mm Min. 0.3 mm
Cutter Feed Speed	Adjustable. (DC motor)
Conveyor flow direction	Selectable via touch screen-Left to Right or Right to Left or Stop
Controls	PLC with touch screen controls.
Top Cutter	Micro Adjustment with Dial Indicator.
Top Cutter Material.	Super wear resistant HSS material with special coating.
Power supply	110VAc or 220VAc 50/60Hz 1 phase.

Please contact: **PTS System (S) Pte Ltd.** email: sales@pts.com.sg www.pts.com.sg
 H/p: 98250975/96390121 Fax: 65-67732262